



**9041 / 9046**

**Transparent**

B4/crystal	
P1/rose	
P2/light blue	
P4/yellow	
P8/green	

**Mat**

Q7/white	
Q8/black	



		insulation class	directly fitted	degree of protection	tension volt	attachment max power	weight lbs/kg	unit price \$
<b>9041</b>				IP 20	120	E12 type B max 28W HALO	0.84 0.380	<b>125</b>
<b>9046</b>				IP 20	120	E12 type B max 28W HALO	0.750 0.600	<b>110</b>
		diameter Ø	diffusor height	length min÷max				
<b>9041</b>		5 <sup>1</sup> / <sub>3</sub> 13,5	5 <sup>2</sup> / <sub>3</sub> 14,5	7 <sup>4</sup> / <sub>5</sub> ÷78 <sup>4</sup> / <sub>5</sub> 20÷200				

**Material**

**Diffusor:** transparent or batch-dyed polycarbonate  
**Rosette:** chrome-plated steel

packaging	quantity	weight lbs/kg	volume m <sup>3</sup>	size cm	size inches
<b>9041</b>	1	1.67/0,760	0,0114	28X22X18	11X8 <sup>2</sup> / <sub>3</sub> X7
<b>9046</b>	1	1.70/0,770	0,0114	28X22X18	11X8 <sup>2</sup> / <sub>3</sub> X7